



Pesi [kg]

Weights

Tolleranze dimensionali: pag. 81
 Pezzi a croce ridotti o con dimensioni
 o spessori particolari: a richiesta (-)

Dimensional tolerances: pag. 81
 Reducing crosses or crosses with special
 thickness and size: on application (-)

D [mm]	M [mm]	NPS	S = SCHEDULE													
			STD	XS	10	20	30	40	60	80	100	120	140	160	XXS	
21,3	25,0	1/2"	0,13	0,20	-	-	-	0,13	-	0,20	-	-	-	0,32	0,40	
26,7	28,5	3/4"	0,20	0,30	-	-	-	0,20	-	0,30	-	-	-	0,45	0,60	
33,4	38,0	1"	0,47	0,61	-	-	-	0,47	-	0,61	-	-	-	1,04	1,30	
42,2	48,0	1 1/4"	0,65	0,91	-	-	-	0,65	-	0,91	-	-	-	1,30	1,56	
48,3	57,0	1 1/2"	0,91	1,17	-	-	-	0,91	-	1,17	-	-	-	1,95	2,35	
60,3	64,0	2"	1,30	1,85	-	-	-	1,30	-	1,85	-	-	-	3,25	3,90	
73,0	76,0	2 1/2"	2,35	2,90	-	-	-	2,35	-	2,90	-	-	-	5,20	7,80	
88,9	86,0	3"	3,50	3,90	-	-	-	3,50	-	3,90	-	-	-	7,80	10,40	
101,6	95,0	3 1/2"	4,60	6,35	-	-	-	4,60	-	6,35	-	-	-	10,40	14,30	
114,3	105,0	4"	5,70	8,30	-	-	-	5,70	-	8,30	-	-	-	13,00	16,90	
141,3	124,0	5"	9,10	12,00	-	-	-	9,10	-	12,00	-	-	-	26,00	31,20	
168,3	143,0	6"	13,00	19,50	-	-	-	13,00	-	19,50	-	-	-	32,50	39,00	
219,1	178,0	8"	24,70	37,60	-	-	-	24,70	-	37,60	-	-	-	67,60	67,60	
273,0	216,0	10"	39,00	62,00	-	-	-	39,00	-	-	-	-	-	111,0	-	
323,8	254,0	12"	61,00	101,0	-	-	-	66,00	-	-	-	-	-	182,0	-	
355,6	279,0	14"	78,00	124,0	-	-	-	-	-	-	-	-	-	-	-	
406,4	305,0	16"	97,00	134,0	-	-	-	-	-	-	-	-	-	-	-	
457,2	343,0	18"	136,0	163,0	-	-	-	-	-	-	-	-	-	-	-	
508,0	381,0	20"	163,0	208,0	-	-	-	-	-	-	-	-	-	-	-	
558,8	419,0	22"	189,0	241,0	-	-	-	-	-	-	-	-	-	-	-	
609,6	431,8	24"	215,0	267,0	-	-	-	-	-	-	-	-	-	-	-	
660,4	495,0	26"	-	-	-	-	-	-	-	-	-	-	-	-	-	
711,2	521,0	28"	-	-	-	-	-	-	-	-	-	-	-	-	-	
762,0	559,0	30"	-	-	-	-	-	-	-	-	-	-	-	-	-	
812,8	597,0	32"	-	-	-	-	-	-	-	-	-	-	-	-	-	
863,6	635,0	34"	-	-	-	-	-	-	-	-	-	-	-	-	-	
914,4	673,0	36"	-	-	-	-	-	-	-	-	-	-	-	-	-	
965,2	711,0	38"	-	-	-	-	-	-	-	-	-	-	-	-	-	
1016,0	749,0	40"	-	-	-	-	-	-	-	-	-	-	-	-	-	
1066,8	711,0	42"	-	-	-	-	-	-	-	-	-	-	-	-	-	
1118,0	762,0	44"	-	-	-	-	-	-	-	-	-	-	-	-	-	
1168,4	800,0	46"	-	-	-	-	-	-	-	-	-	-	-	-	-	
1219,2	838,0	48"	-	-	-	-	-	-	-	-	-	-	-	-	-	