


# Pesi [kg] short radius (R=1 D)

## Weights short radius (R=1 D)



Tolleranze dimensionali: pag. 81  
Curve con dimensioni o spessori particolari: a richiesta (-)

Dimensional tolerances: pag. 81  
Elbows with special thickness and size: on application (-)

D [mm]	NPS	S = SCHEDULE												
		STD	XS	10	20	30	40	60	80	100	120	140	160	XXS
21,3	1/2"	—	—	—	—	—	—	—	—	—	—	—	—	—
26,7	3/4"	—	—	—	—	—	—	—	—	—	—	—	—	—
33,4	1"	0,10	0,13	—	—	—	0,10	—	0,13	—	—	—	0,17	0,21
42,2	1 1/4"	0,17	0,22	—	—	—	0,17	—	0,22	—	—	—	0,28	0,39
48,3	1 1/2"	0,24	0,32	—	—	—	0,24	—	0,32	—	—	—	0,43	0,57
60,3	2"	0,44	0,60	—	—	—	0,44	—	0,60	—	—	—	0,90	1,10
73,0	2 1/2"	0,87	1,15	—	—	—	0,87	—	1,15	—	—	—	1,50	2,05
88,9	3"	1,35	1,83	—	—	—	1,35	—	1,83	—	—	—	2,60	3,10
101,6	3 1/2"	1,90	2,65	—	—	—	1,90	—	2,65	—	—	—	—	—
114,3	4"	2,60	3,60	—	—	—	2,60	—	3,60	—	4,60	—	5,40	6,60
141,3	5"	4,40	6,20	—	—	—	4,40	—	6,20	—	8,00	—	9,90	11,50
168,3	6"	7,00	10,00	—	—	—	7,00	—	10,00	—	13,00	—	16,00	19,00
219,1	8"	14,00	21,00	—	11,00	12,00	14,00	17,00	21,00	25,00	29,00	33,00	36,00	35,00
273,0	10"	24,00	33,00	—	17,00	21,00	24,00	33,00	39,00	46,00	54,00	62,00	70,00	62,00
323,8	12"	36,00	47,00	—	24,00	32,00	39,00	53,00	64,00	77,00	90,00	100,0	115,0	90,00
355,6	14"	46,00	61,00	31,00	39,00	46,00	53,00	71,00	90,00	110,0	126,0	142,0	160,0	—
406,4	16"	60,00	79,00	40,00	50,00	60,00	79,00	103,0	130,0	157,0	184,0	213,0	235,0	—
457,2	18"	76,00	100,0	51,00	64,00	88,00	113,0	148,0	185,0	223,0	262,0	300,0	332,0	—
508,0	20"	94,00	124,0	63,00	94,00	124,0	147,0	200,0	250,0	305,0	353,0	408,0	452,0	—
558,8	22"	114,0	151,0	77,00	114,0	151,0	—	260,0	330,0	400,0	464,0	530,0	591,0	—
609,6	24"	136,0	180,0	97,00	136,0	202,0	245,0	341,0	424,0	526,0	614,0	691,0	775,0	—
660,4	26"	158,0	210,0	—	—	—	—	—	—	—	—	—	—	—
711,2	28"	184,0	244,0	—	—	—	—	—	—	—	—	—	—	—
762,0	30"	211,0	281,0	—	—	—	—	—	—	—	—	—	—	—
812,8	32"	240,0	320,0	—	—	—	—	—	—	—	—	—	—	—
863,6	34"	271,0	361,0	—	—	—	—	—	—	—	—	—	—	—
914,4	36"	304,0	405,0	—	—	—	—	—	—	—	—	—	—	—
965,0	38"	—	—	—	—	—	—	—	—	—	—	—	—	—
1016,0	40"	376,0	501,0	—	—	—	—	—	—	—	—	—	—	—
1066,8	42"	—	—	—	—	—	—	—	—	—	—	—	—	—
1118,0	44"	—	—	—	—	—	—	—	—	—	—	—	—	—
1168,4	46"	456,0	—	—	—	—	—	—	—	—	—	—	—	—
1219,2	48"	—	—	—	—	—	—	—	—	—	—	—	—	—