



Pesi [kg]

Weights

Tolleranze dimensionali: pag. 81
 Riduzioni con dimensioni o spessori particolari: a richiesta (-)

Dimensional tolerances: pag. 81
 Reducers with special thickness and size: on application (-)

D [mm]	H [mm]	NPS SERIES	S = SCHEDULE												
			STD	XS	10	20	30	40	60	80	100	120	140	160	XXS
21,3	—	1/2"	—	—	—	—	—	—	—	—	—	—	—	—	—
26,7	38,0	3/4"	0,09	0,16	—	—	—	0,09	—	0,16	—	—	—	—	—
33,4	51,0	1"	0,10	0,20	—	—	—	0,10	—	0,20	—	—	—	0,25	—
42,2	51,0	1 1/4"	0,20	0,30	—	—	—	0,20	—	0,30	—	—	—	0,30	0,35
48,3	64,0	1 1/2"	0,30	0,40	—	—	—	0,30	—	0,40	—	—	—	0,50	0,45
60,3	76,0	2"	0,40	0,60	—	—	—	0,40	—	0,60	—	—	—	1,10	0,70
73,0	89,0	2 1/2"	0,80	1,00	—	—	—	0,80	—	1,00	—	—	—	1,60	1,30
88,9	89,0	3"	1,00	1,40	—	—	—	1,00	—	1,40	—	—	—	2,00	2,10
101,6	102,0	3 1/2"	1,40	2,00	—	—	—	1,40	—	2,00	—	—	—	2,80	2,60
114,3	102,0	4"	1,60	2,20	—	—	—	1,60	—	2,20	—	3,00	—	4,00	3,70
141,3	127,0	5"	2,80	4,00	—	—	—	2,80	—	4,00	—	5,60	—	7,00	4,70
168,3	140,0	6"	4,00	6,00	—	—	—	4,00	—	6,00	—	8,30	—	10,50	8,00
219,1	152,0	8"	6,50	9,90	—	5,80	6,20	6,50	8,60	9,90	12,60	15,00	17,00	18,80	12,30
273,0	171,0	10"	10,00	14,00	—	9,00	10,00	10,00	14,00	18,00	22,00	26,00	30,00	32,00	18,00
323,8	203,0	12"	15,00	19,00	—	13,00	14,00	16,00	23,00	29,00	35,00	41,00	46,00	56,00	34,00
355,6	330,0	14"	30,00	36,00	25,00	28,00	30,00	34,00	47,00	60,00	72,00	82,00	92,00	104,0	46,00
406,4	356,0	16"	37,00	48,00	33,00	35,00	37,00	48,00	62,00	82,00	98,00	114,0	131,0	145,0	—
457,2	381,0	18"	45,00	58,00	40,00	42,00	54,00	68,00	90,00	110,0	132,0	150,0	172,0	195,0	—
508,0	508,0	20"	68,00	86,00	62,00	68,00	86,00	105,0	140,0	173,0	210,0	240,0	275,0	310,0	—
558,8	508,0	22"	72,00	93,00	67,00	72,00	93,00	130,0	—	—	—	—	—	450,0	—
609,6	508,0	24"	70,00	77,00	115,0	143,0	205,0	257,0	315,0	380,0	440,0	480,0	—	—	—
660,4	610,0	26"	100,0	130,0	—	130,0	—	—	—	—	—	—	—	—	—
711,2	610,0	28"	105,0	140,0	—	140,0	—	—	—	—	—	—	—	—	—
762,0	610,0	30"	110,0	145,0	—	—	—	—	—	—	—	—	—	—	—
812,8	610,0	32"	125,0	150,0	—	—	—	—	—	—	—	—	—	—	—
864,0	610,0	34"	130,0	158,0	—	—	—	—	—	—	—	—	—	—	—
914,4	610,0	36"	135,0	175,0	—	—	—	—	—	—	—	—	—	—	—
965,0	610,0	38"	—	—	—	—	—	—	—	—	—	—	—	—	—
1016,0	610,0	40"	—	—	—	—	—	—	—	—	—	—	—	—	—
1066,8	610,0	42"	—	—	—	—	—	—	—	—	—	—	—	—	—
1118,0	610,0	44"	—	—	—	—	—	—	—	—	—	—	—	—	—
1168,0	711,0	46"	—	—	—	—	—	—	—	—	—	—	—	—	—
1219,0	711,0	48"	—	—	—	—	—	—	—	—	—	—	—	—	—